

# New Jersey DOT

## Section 919.01

Application	Class	Suggested WINFAB product	
		Woven	Nonwoven
Subsurface Drainage <15% fines	2	WINFAB 2404	-
Subsurface Drainage 15-50% fines	2	WINFAB 2199	-
Subsurface Drainage >50% fines	2	WINFAB 2199	-
Stabilization	1	WINFAB 315W	WINFAB 800N
Erosion Control <sup>1,2</sup> <15% fines	1	WINFAB 2404	WINFAB 800N
Erosion Control <sup>1,2</sup> 15-50% fines	1	-	WINFAB 800N
Erosion Control <sup>1,2</sup> >50% fines	1	-	WINFAB 800N
Erosion Control <sup>1,2</sup> <15% fines	2	WINFAB 2404	WINFAB 600N
Erosion Control <sup>1,2</sup> 15-50% fines	2	WINFAB 2199	WINFAB 600N
Erosion Control <sup>1,2</sup> >50% fines	2	WINFAB 2199	WINFAB 600N
Paving	-	-	WINFAB 400NP

<sup>1</sup> For inlet filters, use Class 2 for woven monofilament geotextiles or Class 1 for all other types of geotextiles.

<sup>2</sup> For inlet filter, Type 2, in addition to the AASHTO M 288 requirements, ensure that the geotextile's burst strength is at least 650 pounds per square inch when tested according to ASTM D 3786.

**Disclaimer:** Willacochee Industrial Fabrics assumes no liability for the completeness or accuracy of this information or the ultimate use of this information. Willacochee Industrial Fabrics disclaims any and all implied, expressed, or statutory standards, guarantees, or warranties. This includes without limitation any implied warranty as to merchantability or fitness for a particular purpose or arising from a course of dealing or usage of trade as to equipment, materials, or information furnished herewith. This document should not be construed as engineering advice. Always consult the project engineer for project specific requirements. The end user assumes sole responsibility for the use of this information and product. The products listed above are subject to change without notice.

© 2015 Willacochee Industrial Fabrics, Inc.

**Willacochee Industrial Fabrics, Inc.**

PO Box 599 • 769 West Main Street • Willacochee, GA 31650

Ph: (912) 534-5757 • Fax: (912) 534-5533

